



# Nylock Nuts

## acc. to DIN 985

Material: steel  
 Finish: zinc plated  
 Tensile Strength: 8

### UNC

Thread Ø inch	Pitch per inch	A/F inch	Height min. - max. mm	Art. No.	Pack Qty.
1/4	20	7/16	7.57 - 8.33	<b>0375 14</b>	25
5/16	18	31/64	8.36 - 64	<b>0375 516</b>	
3/8	16	9/16	11.13 - 11.89	<b>0375 38</b>	
7/16	14	11/16	11.13 - 11.89	<b>0375 716</b>	
1/2	13	3/4	14.71 - 15.47	<b>0375 12</b>	50
9/16	12	7/8	15.90 - 16.66	<b>0375 916</b>	
5/8	11	15/16	18.67 - 19.43	<b>0375 58</b>	25
3/4	10	1 71/16	21.84 - 22.60	<b>0375 34</b>	
7/8	9	1 71/ 4	24.61 - 25.37	<b>0375 78</b>	
1	8	1 27/64	25.81 - 27.38	<b>0375 1</b>	

### UNF

Thread Ø inch	Pitch per inch	A/F inch	Height min. - max. mm	Art. No.	Pack Qty.
1/4	28	7/16	7.57 - 8.33	<b>0378 14</b>	25
5/16	24	31/64	8.36 - 64	<b>0378 516</b>	
3/8	24	9/16	11.13 - 11.89	<b>0378 38</b>	
7/16	20	11/16	11.13 - 11.89	<b>0378 716</b>	
1/2	20	3/4	14.71 - 15.47	<b>0378 12</b>	
9/16	18	7/8	15.90 - 16.66	<b>0378 916</b>	
5/8	18	15/16	18.67 - 19.43	<b>0378 58</b>	
3/4	16	1 71/16	21.84 - 22.60	<b>0378 34</b>	
7/8	14	1 71/ 4	24.61 - 25.37	<b>0378 78</b>	
1	12	1 27/64	25.81 - 27.38	<b>0378 1</b>	



# Rubnuts

Size	Ø x length mm	Art. No.	Pack Qty.
M4	7.9 x 12.6	<b>5006 01</b>	10
M5	9.6 x 14.1	<b>5006 02</b>	
M5	9.6 x 21.5	<b>5006 03</b>	
M6	12.7 x 16.0	<b>5006 04</b>	
M6	12.7 x 26.7	<b>5006 05</b>	
M8	15.9 x 18.3	<b>5006 07</b>	