

# GLASS AKTIV SEALANT



## Special sealant for sealing self cleaning glass.

To seal self-cleaning/photocatalytic glass with a titanium dioxide coating, a special MS polymer-based sealant system, which is ideal and tested for this purpose, must be used. Conventional silicone sealants can dissolve the glass coating.

► Safety tested.

### **Your advantage:**

- Tested window glazing from the COT Laboratorium pursuant to DIN EN ISO 11600 (building construction joint sealants).

► Approval for self-cleaning glass.

### **Your advantage:**

- Approved and registered for Pilkington Activ TM.

### **Other advantages:**

- Can be painted over; compatible with paint.
- UV and weather-resistant.
- Odourless.
- Silicone-free.
- Building material class B2 according to DIN 4102.

Description	Contents ml	Colour	Art. No.	Pack/Qty
Cartridge	290	white	<b>0893 350 801</b>	1/12
Cartridge	290	grey	<b>0893 350 802</b>	1/12
Cartridge	290	black	<b>0893 350 803</b>	1/12

## Use:

glass sealing, sealing of self-cleaning glass, laminated safety glass and window connection joints.

## Technical data:

Maximum absorption of continuous movement	25% of the joint width
Skin formation time (at 23°C/50 rel.humidity)	5 - 10 minutes
Hardening (at 23°C/50 rel.humidity)	approx. 2 mm after 24 hours
Thermal stability	-40°C to 90°C
Shelf life	12 months

Sealing Smoothing Agent

**Art. No: 0893 3**

Cartridge Gun

**Art. No: 1892 ...**

Spatula

**Art. No: 0891 182**

Cartridge Knife

**Art. No: 0715 66 09**

With this information we want to advise you to the best of our knowledge based on our tests and experience. Preliminary testing required! For further information see the technical data leaflet.