



- 5 litres
- High strength
- High temperature range 120°C
- Economic
- No waste or transport issues
- No propellants
- Cost effective
- Bonds a large variety of materials

**Art. No. 0893 000 007** (red)

**Art. No. 0893 000 008** (clear)  
Pack Qty. 1

# Solvtac Sprayable Contact Adhesive

Solvtac is a non flammable, sprayable synthetic rubber contact adhesive with an aggressive tack and high strength bond. Suitable for bonding a wide range of materials, chipboard, flexible foams, fabrics, head linings, upholstery materials and paddings, MDF, hardboards, laminates, GRP, metals and plastic laminates to a variety of core materials.

**NOTE: Not suitable for use on plasticised PVC**

## Technical Properties:

Base	Synthetic rubber
Solids	24 -/+ 2%
Viscosity	250-400cP at 20°C
Colour	Clear and red
Temperature range	120°C
Working temperature	10°C to 20°C
Tack life	1 - 20 minutes
Coverage	10-13m sq / ltr
Cleaner	Solvent cleaner 1890 100 026
Shelf life	12 months at 5°C - 25°C



# Suction Feed Spray Gun for Solvtac Adhesive

- Economic
- 1 litre pot capacity
- Low cost
- Requires 2.5 bar from an air compressor
- Adjustable coat weight
- Adjustable spray pattern size
- Easy to clean and maintain.

**Art. No. 0891 100 203**

Pack Qty. 1

## Associated parts



Quick release  
1/4" coupling  
**Art. No. 0699 201 4**

Quick release  
9mm coupling  
**Art. No. 0699 129**

9mm Hose  
**Art. No. 0699 909 1**