



Web Spray Contact Adhesive

bonds to a variety of substrates

- High strength.
- Colour: clear or red.
- Flexible.
- Water resistant.
- Temperature resistant to 93°C.
- Disposable canister.

Suitable for:

Bonding laminates, edge banding, veneering, foam bonding, bonding headlinings, etc., so is suitable for shopfitters, scene makers, exhibition companies, general workshop use, caravan/campervan makers and any other use where contact adhesive is applied. It will also bond to a variety of substrates such as wood, fibreglass, particle board, plywood, some plastics, cork etc. This system is quick and easy to apply and extremely cost effective. Ideal for workshop or site work.

Description	Contents	Art. No.	Pack Qty.
Canister clear	17kg	0893 100 017	1
Canister red		0893 100 019	
Spray gun	n/a	1891 602 002	
3.5 meter clear hose	n/a	1891 602 011	

Application:

Spray an even "web" of adhesive to cover both surfaces to be joined. Do not spray over wet. Allow to dry for 2 to 4 minutes (21°C and 50% RH) and to become "tacky". The open time of this product at this stage can be several hours, providing surfaces are kept free of dust, sawdust etc. High humidity or low temperatures can slow drying times. For porous and crucial joints, such as edge bandings, it is recommended to apply a second coat after the first has become tacky. Place surfaces together and apply an even pressure to achieve a strong bond. Full strength is achieved after 24hrs. For best results, adhesive and substrates should be at 15°C or higher. Also, ensure that surfaces are dry, free of dirt, grease, oils and other solvents.

Technical:

Colour	Clear
Viscosity	1.19 ± 0.02
Application method:	Spray
Application temp:	15°C or higher
Coverage:	206 ² ft (68m ²)
Storage:	1 year, unopened if kept between 16 and 38°C out of direct sunlight.
Packaging:	17kg canister (disposable)

Note: Not suitable for use on colourcore®.
Not suitable for use on plasticised PVC or expanded polystyrene