

REPLAST

Complete system for professional repairs of plastic parts.



Description	Contents	Art. No.	Pack Qty.
Replast adhesive set	*	0893 500 0	1
Plastic cleaner	500ml	0893 500 1	1
Plastic primer	200ml	0893 500 2	1
Fast 2C-plastic adhesive	50ml	0893 500 3	1
Universal 2C-plastic adhesive	50ml	0893 500 4	1
Superfast 2C-plastic adhesive	50ml	0893 500 5	1
Reinforcement tape	3.5m	0893 500 6	1
Contour film	3.5m	0893 500 7	1
Positive mixer	-	0891 486	25
Application gun	-	0891 893 485	1

*Set = 1 plastic cleaner, 1 plastic primer, 2 Fast 2C-plastic adhesive, 4 Universal 2C-plastic adhesive, 1 reinforcement tape, 1 contour film, 25 positive mixer, 1 application gun.

Areas of application:

Passenger vehicles:

Spoilers, radiator grill, panelling clips, bumpers, brackets on headlamps and radiator, etc.

HGVs and buses:

Skirts, bumpers, air intake duct, wheel arches, etc.

Motorbikes:

All panelling.

Technical data:

	Universal 2C-plastic adhesive	Fast 2C-plastic adhesive	Superfast 2C-plastic adhesive
Application time	3.5 minutes	1.5 minutes	25 seconds
Can be sanded at 23°C after	30 minutes	10 minutes	5 minutes
Shore hardness D	79	79	79
Colour	black	black	black

This information is intended as a recommendation only, based on our experience. Preliminary tests to verify material compatibility should be carried out. The cleaning and care instructions of the manufacturer must be observed!

▶ An adhesive for almost all types of plastic.*

The advantages for you:

- No complex treatments of different types of adhesives.
- Usable for repairs and structural bonding.

▶ Special positive mixer

The advantages for you:

- Optimal mixing for small volumes.
- Low loss of adhesive (waste).

▶ Cures quickly.

The advantage for you:

- Further processing, e.g. grinding, possible after minimum period of time.

▶ Superb chemical resistance.

The advantage for you:

- Resistant to many liquids such as petrol, many lubricants as well as ethyl acetate.

▶ Solvent-free adhesive.

Transparent plastic adhesive

Art. No. 0893 500 8

Pack Qty. 1

- For colourless bonding of transparent or coloured plastic parts.
- Application time 3 minutes.
- Suitable for polycarbonate (PC) and plexiglas (PMMA).
- Weight: 50ml.

***Note:**

Due in part to the coatings and release agents used when manufacturing plastics, in isolated cases there may be adhesion problems.

Not suitable for the plastics PE (polyethylene) and PP (polypropylene) and PTFE (polytetrafluoroethylene). If necessary, check material compatibility in an inconspicuous place.