

HHS 2000

Extremely high-pressure resistant partially synthetic oil



Contents ml	Art. No.	P. Qty.
500	0893 106	1/6/12/24
150	0893 106 1	1/12

Applications:

Suitable for universal lubrication and under high pressure loads, e.g. shift, throttle and clutch linkages, Bowden cables, hinges, deflection levers etc.

Versatile lubricating oil due to its combination of balanced, matched properties.

- ▶ High-pressure resistant
Your advantage:
 - Extraordinarily tear-resistant lubricating film with outstanding noise and vibration damping properties.
- ▶ High creep capacity
Your advantage:
 - Excellent lubricating properties with close tolerances. Reliably protects against corrosion.
- ▶ Active adhesive effective
Your advantage:
 - No throwing off of the lubricant with turning and rotating parts.
- ▶ Good material compatibility
Your advantages:
 - Compatible with O-rings and X-rings, as well as with plastics.
 - Behaves neutrally toward painted surfaces.
- ▶ Splash and saltwater-resistant, withstands weak acids and alkaline solutions
- ▶ Contains no silicone, resin or acid
- ▶ Operating temperature range: -35°C to 180°C
Temporarily: 200°C
- ▶ Colour: yellowish

HHS Clean
Art. No. 0893 106 10

This information is intended as a recommendation only, based on our experience. Preliminary tests to verify material compatibility should be carried out. The cleaning and care instructions of the manufacturer must be observed!