

HHS GREASE

High-quality, white long-term maintenance grease containing PTFE



Contents ml	Art. No.	P. Qty.
400	0893 106 7	1/6/12/24

Applications:

Suitable for lubrication during maintenance and inspection work, e.g. hinges, joints, slide rails etc.

Sealing behaviour against dirt and splash water

The grease forms a sealing grease collar against moisture and dirt particles between the opposing body and the base body. The dirt cannot reach the lubricating point, ensuring long-term lubrication. The lubricating intervals extended in this way are only possible with good cleaning of the lubricating point, and we therefore recommend thorough cleaning with **0893 106 10**, before every use.

Versatile white long-term grease with outstanding material compatibility properties.

- ▶ Long life
Your advantage:
 - Excellent sealing behaviour against moisture and dirt. Therefore, top oxidation stability and extension of lubricating intervals. Excellent corrosion protection.
- ▶ Outstanding material compatibility
Your advantages:
 - Excellent compatibility (plastic).
 - Behaves neutrally toward painted surfaces.
- ▶ With PTFE solid lubricant share
Your advantages:
 - After grease film tears off, PTFE takes over lubrication (emergency running property).
 - High thermal stability.
- ▶ With special white pigmentation
Your advantage:
 - Optimum recognition of lubrication points during maintenance and inspection.
- ▶ Splash and saltwater-resistant, withstands weak acids and alkaline solutions
- ▶ Contains no silicone, resin or acid
- ▶ Operating temperature range: -15°C to 130°C
Temporarily: 200°C
- ▶ Colour: bright white

HHS Clean
Art. No. 0893 106 10

This information is intended as a recommendation only, based on our experience. Preliminary tests to verify material compatibility should be carried out. The cleaning and care instructions of the manufacturer must be observed!