

MULTI-PURPOSE GREASE



Description grease	Contents	Art. No.	Pack Qty.
Multi-purpose Grease I	400 g	0893 870 1	1/12
Multi-purpose Grease II	400 g	0893 871 1	

Note: Store upright in a cool and dry place.

Technical Data

	M.-P. Grease I 0893 870 1	M.-P. Grease II 0893 871 1
Areas of application	For vehicles subject to light loads and machine elements, such as anti-friction bearings and sliding bearings, shafts, spindles, electrical motor bearings, ball and roller bearings, suspensions, etc.	For anti-friction bearings, sliding bearings, ball and roller bearings, shafts, turning knuckles, live rings, slide paths and guides, splined shafts, joint rods, hinges, hydraulic units, etc. subject to middle and heavy loads.
Saponification base	Lithium 12 Hydroxystearat	Lithium 12 Hydroxystearat
Colour	yellow	grey-black
NLGI class (DIN 51818)	2	2
Temperature range	-30°C to 130°C	-20°C to 130°C
Basic oil viscosity at 40°C	130 mm ² /s	60 mm ² /s
Drop point (DIN ISO 2176)	180°C	190°C
Worked penetration (DIN ISO 2137)	280	280
Corrosion protection (SKF Emscor test, DIN 51802)	0	0
VKA welding load (51350)	1800 N	2400 N
Description acc. to DIN 51502	K 2K-30	KPF 2K-30

MULTI-PURPOSE GREASE I

- ▶ Lithium saponified universal lubricating grease with mineral-oil base

Your advantages:

- Stable against working and oxidation-resistant.
- Excellent sealing plus dust and dirt repellent.
- Good adhesion.
- Silicone and resin free.
- Comes in practical pull off cartridge.

MULTI-PURPOSE GREASE II

- ▶ Lithium saponified, high pressure resistant graphite grease with EP additives

Your advantages:

- High-pressure resistant via EP additive.
- Excellent antiseizing properties via graphite.
- Good sealing effect and corrosion protection.
- Very good dust, dirt and water repellent properties.
- Silicone and resin-free.
- Comes in practical pull off cartridge

Note:

Greases are delivered in plastic cartridges. The plastic cartridges improve storage (they prevent the grease from oozing out in high temperature conditions). Store cartridges upright in a cool, dry place. The operating instructions of the manufacturers must be observed. For further information see the technical information leaflet.

This information is intended as a recommendation only, based on our experience. Preliminary tests to verify material compatibility should be carried out. The cleaning and care instructions of the manufacturer must be observed!