



Standard Hot Melt Glue Gun

- Standard Hot Melt 193°C
- Ergonomically designed
- Long trigger for ease of feed
- Light weight: 300g
- Glue flow: 750g/hr
- 240V / 80W

Areas of use

Upholstery, textiles (heavy duty only not rayon or silk), electronics, spot tacking while soldering, graphic art (not on photos), kitchen cupboard bumpers, food industry (FDA approved), carton sealing, general packaging, tile bonding, plastic/wood trims (kitchen/bedrooms), spot bonding while other adhesives go off, metal trims, badge mounting, picture frame makers, electronic potting (not permanent), electric cable spot bonding (not permanent), product assembly, wood to wood, wood to plastic, plastic to metal, plastic to plastic (rigid).

Description	Art. No.	Pack Qty.
Standard hot melt glue gun	0702 623	1
Standard hot melt glue sticks -clear	0890 100 052	30 pieces

Technical Data

Type	Synthetic base
Colour	Colourless translucent
Viscosity	11000 mPas 180°
Softening point	85°C
Molten tack	Very high
Open time	45 seconds (approx) (BS5350 part H4)

Glue sticks

- A universal hot melt with long open time and excellent adhesion properties to many surfaces including fabrics (natural and synthetic), wood, plastic and a variety of surface finishes.
- Especially recommended for upholstery applications
- Set time: 20 - 30 seconds.

Size	Art. No.	Pack Qty.
12 x 285 mm	1890 100 054	5 kgs
11.5 x 180 mm	0890 100 054	appr. 50 pcs
Standard low melt glue sticks -white	1890 100 059	30 pieces