According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : WIT-PE 1000, 585ml (B)

Product code : 5918605585 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub: Construction material, Dual-component adhesive

stance/Mixture Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Wurth UK Ltd

1 Centurion Way Erith, Kent

Telephone : +44 (0)3300 555 444

Telefax : +44 (0)3300 555 666

E-mail address of person responsible for the SDS

prodsafe@wuerth.com

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Sub-category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms





Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements : Prevention:

P260 Do not breathe dust or mist.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

Hazardous components which must be listed on the label:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine

m-phenylenebis(methylamine)

2,4,6-Tris{(Dimethylamino)methyl}phenol

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Amines

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Quartz (SiO2)	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 30 - < 50
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25513-64-8 247-063-2 01-2119560598-25	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 30 - < 50
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 5 - < 10
2,4,6- Tris{(Dimethylamino)methyl}phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 5 - < 10
p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4)	104-15-4 203-180-0 016-030-00-2 01-2119538811-39	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 ————————————————————————————————————	>= 3 - < 5

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25513-64-8

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention immediately. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control centre immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Causes digestive tract burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides Silicon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing dust, fume, gas, mist, vapours or spray.

Do not breathe dust or mist.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national

regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives

Storage period : 18 Months

Recommended storage tem- :

perature

5 - 25 °C

7.3 Specific end use(s)

Specific use(s) : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3 (Silica)	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA (Respirable dust)	0.1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz (SiO2)

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
m- phe- nylenebis(methylamin e)	Workers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0.2 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.33 mg/kg bw/day
2,2,4(or 2,4,4)- Trimethylhexane-1,6- diamine	Consumers	Ingestion	Long-term systemic effects	0.05 mg/kg bw/day
p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4)	Workers	Inhalation	Long-term systemic effects	53.6 mg/m3
	Workers	Skin contact	Long-term systemic effects	7.6 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8.7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2.5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2.5 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
2,4,6-	Fresh water	0.084 mg/l
Tris{(Dimethylamino)methyl}phen		
ol		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

	Marine water	0.0084 mg/l
	Sewage treatment plant	0.2 mg/l
	Intermittent use/release	0.84 mg/l
m-phenylenebis(methylamine)	Fresh water	0.094 mg/l
	Marine sediment	0.0094 mg/l
	Intermittent use/release	0.152 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0.43 mg/kg
	Marine sediment	0.043 mg/kg
	Soil	0.045 mg/kg
	Fresh water sediment	0.43 mg/kg
2,2,4(or 2,4,4)-Trimethylhexane- 1,6-diamine	Fresh water	0.102 mg/l
	Marine water	0.01 mg/l
	Freshwater - intermittent	0.315 mg/l
	Sewage treatment plant	72 mg/l
	Fresh water sediment	0.622 mg/kg dry
		weight (d.w.)
	Marine sediment	0.062 mg/kg dry
		weight (d.w.)
	Soil	10 mg/kg dry
		weight (d.w.)
p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4)	Fresh water	0.073 mg/l
	Freshwater - intermittent	0.73 mg/l
	Marine water	0.0073 mg/l
	Sewage treatment plant	58 mg/l
	Fresh water sediment	0.0577 mg/kg dry weight (d.w.)
	Marine sediment	0.00577 mg/kg
		dry weight (d.w.)
	Soil	0.016 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn. If splashes are likely to occur, wear:

Face-shield

Equipment should conform to BS EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0.7 mm

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Directive : Equipment should conform to BS EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to BS EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : grey, red

Odour : characteristic

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 1.42 g/cm³ (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Skir

exposure

Skin contact Ingestion

Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,512 mg/kg

Method: Calculation method

Acute inhalation toxicity : Assessment: Not corrosive to the respiratory tract

Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Quartz (SiO2):

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 (Rat): 910 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 (Rat): > 200 - < 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): > 3,100 mg/kg

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Acute oral toxicity : LD50 (Rat): 1,653 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Acute oral toxicity : LD50 (Rat): 1,410 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes severe burns.

Components:

Quartz (SiO2):

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 3 minutes or less of exposure

m-phenylenebis(methylamine):

Species : Rat

Result : Corrosive after 3 minutes to 1 hour of exposure

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 1 to 4 hours of exposure

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Quartz (SiO2):

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : Based on data from similar materials

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

m-phenylenebis(methylamine):

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Species : Rabbit

Result : Irreversible effects on the eye

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in hu-

mans

m-phenylenebis(methylamine):

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Test Type : Maximisation Test

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : equivocal

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : Regulation (EC) No. 440/2008, Annex, B.6

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Bacterial reverse mutation assay (AMES) Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Hamster

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 475

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

m-phenylenebis(methylamine):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Species : Mouse
Application Route : Skin contact
Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Reproductive toxicity

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Ingestion

Result: negative

m-phenylenebis(methylamine):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

Quartz (SiO2):

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Quartz (SiO2):

Species : Humans LOAEL : 0.053 mg/m3 Application Route : Inhalation

Remarks : These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rat
NOAEL : 10 mg/kg
LOAEL : 60 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

m-phenylenebis(methylamine):

Species : Rat NOAEL : 150 mg/kg Application Route : Ingestion

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Exposure time : 28 Days

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Species : Rat

NOAEL : 15 mg/kg

Application Route : Ingestion

Exposure time : 43 Days

Method : OECD Test Guideline 422

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Species : Rat

NOAEL : >= 500 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Quartz (SiO2):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 731 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 174 mg/l

Exposure time: 48 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 31.5 mg/l

Exposure time: 24 h Method: DIN 38412

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 43.5

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 16

mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 72 mg/l

Exposure time: 17 h Method: DIN 38 412 Part 8

Toxicity to fish (Chronic tox-

icity)

NOEC: >= 10.9 mg/l Exposure time: 30 d

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EC10: 1.02 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 87.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 15.2 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 33.3 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 22.9 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

ErC50 (Selenastrum capricornutum (green algae)): 32.1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1,000 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 4.7 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 84 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

plants Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 6.25 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : 2 mg/l

Exposure time: 28 d

Method: OECD Test Guideline 301D

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 325 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10 -

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 : 240 mg/l

Exposure time: 3 h

12.2 Persistence and degradability

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 7 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.A.

m-phenylenebis(methylamine):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 49 % Exposure time: 28 d

Method: OECD Test Guideline 301B

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4 % Exposure time: 28 d

Method: OECD Test Guideline 301D

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301B

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Partition coefficient: n-

octanol/water

: log Pow: -0.3

m-phenylenebis(methylamine):

Partition coefficient: n-

octanol/water

log Pow: 0.18

2,4,6-Tris{(Dimethylamino)methyl}phenol:

Partition coefficient: n-

octanol/water

: log Pow: 0.219

p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4):

Partition coefficient: n- : log Pow: -0.96

octanol/water Method: Regulation (EC) No. 440/2008, Annex, A.8

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

unused product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 3259
ADR : UN 3259
RID : UN 3259
IMDG : UN 3259
IATA : UN 3259

14.2 UN proper shipping name

ADN : AMINES, SOLID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-

Trimethylhexane-1,6-diamine)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

ADR : AMINES, SOLID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-

Trimethylhexane-1,6-diamine)

RID : AMINES, SOLID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-

Trimethylhexane-1,6-diamine)

IMDG : AMINES, SOLID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-

Trimethylhexane-1,6-diamine)

IATA : Amines, solid, corrosive, n.o.s.

(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-

Trimethylhexane-1,6-diamine)

14.3 Transport hazard class(es)

 ADN
 : 8

 ADR
 : 8

 RID
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADN

Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8

ADR

Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID

Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 863

aircraft)

Packing instruction (LQ) : Y844
Packing group : II

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen- : 859

ger aircraft)

Packing instruction (LQ) : Y844
Packing group : II

Labels : Corrosive

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

on : Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Not applicable

GB Export and import of hazardous chemicals - Prior :

24 / 26

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

Informed Consent (PIC) Regulation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 21.7 %, 308.2 g/l

Remarks: VOC content excluding water

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H372 : Causes damage to organs through prolonged or repeated

exposure if inhaled.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Skin Corr. : Skin corrosion Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2004/37/EC / TWA : Long term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



WIT-PE 1000, 585ml (B)

Version Revision Date: SDS Number: Date of last issue: -

1.0 24.03.2022 10643893-00001 Date of first issue: 24.03.2022

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Acute Tox. 4	H302	Calculation method
Skin Corr. 1A	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN