

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : WIT-UH 300 - 420 ML (comp. A)
Product code : 5918500420

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives and/or sealants
Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0
Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version
6.0

Revision Date:
13.01.2021

SDS Number:
1476873-00007

Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Tetramethylene dimethacrylate

Methacrylic acid, monoester with propane-1,2-diol

4-tert-Butylpyrocatechol

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 20 - < 30
Tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30	Skin Sens. 1B; H317	>= 10 - < 20
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3 01-2119490226-37	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0,1 - < 1
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3 254-075-1	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 0,25 - < 1
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9	Repr. 2; H361d Aquatic Chronic 3; H412	>= 0,25 - < 1
4-tert-Butylpyrocatechol	98-29-3 202-653-9 01-2119548368-28	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,1 - < 0,25

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

		Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- || Suitable extinguishing media : Water spray
Alcohol-resistant foam

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

Carbon dioxide (CO ₂) Dry chemical	
Unsuitable extinguishing media	: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapours or spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
- Storage class (TRGS 510) : 11, Combustible Solids
- Recommended storage temperature : 5 - 25 °C

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable)	0,1 mg/m ³	2004/37/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version
6.0

Revision Date:
13.01.2021

SDS Number:
1476873-00007

Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

		dust)		
	Further information: Carcinogens or mutagens			
Dimethyl siloxane reaction with silica	67762-90-7	AGW (Inhalable fraction)	4 mg/m ³ (Silica)	DE TRGS 900
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz (SiO₂)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Tetramethylene dimethacrylate	Workers	Inhalation	Long-term systemic effects	14,5 mg/m ³
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,3 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
	Methacrylic acid, monoester with propane-1,2-diol	Workers	Inhalation	Long-term systemic effects
Workers		Skin contact	Long-term systemic effects	4,2 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	8,8 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
	1,1'-(p-tolylimino)dipropan-2-ol	Workers	Inhalation	Long-term systemic effects
Workers		Skin contact	Long-term systemic effects	0,6 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	0,4 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,3 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day
	4-tert-Butylpyrocatechol	Workers	Inhalation	Long-term systemic effects
Consumers		Inhalation	Long-term systemic effects	406 µg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version
6.0

Revision Date:
13.01.2021

SDS Number:
1476873-00007

Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

			effects	
	Consumers	Ingestion	Long-term systemic effects	0,117 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	1,6 mg/kg bw/day
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	Workers	Inhalation	Long-term systemic effects	17,62 mg/m3
	Workers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,35 mg/m3
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Tetramethylene dimethacrylate	Fresh water	0,087 mg/l
	Marine water	0,009 mg/l
	Intermittent use/release	0,098 mg/l
	Sewage treatment plant	20 mg/l
	Fresh water sediment	3,12 mg/kg
	Marine sediment	0,312 mg/kg
Methacrylic acid, monoester with propane-1,2-diol	Soil	0,573 mg/kg
	Fresh water	0,904 mg/l
	Marine water	0,904 mg/l
	Intermittent use/release	0,972 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	6,28 mg/kg
1,1'-(p-tolylimino)dipropan-2-ol	Marine sediment	6,28 mg/kg
	Soil	0,727 mg/kg
	Fresh water	0,017 mg/l
	Marine water	0,0017 mg/l
	Intermittent use/release	0,17 mg/l
	Sewage treatment plant	199,5 mg/l
4-tert-Butylpyrocatechol	Fresh water sediment	0,0782 mg/kg
	Marine sediment	0,00782 mg/kg
	Soil	0,005 mg/kg
	Fresh water	1,2 µg/l
	Freshwater - intermittent	1,2 µg/l
	Marine water	0,12 µg/l
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	Sewage treatment plant	0,16 mg/l
	Fresh water sediment	0,0069 mg/kg dry weight (d.w.)
	Marine sediment	0,00069 mg/kg dry weight (d.w.)
	Soil	0,00068 mg/kg dry weight (d.w.)
	Fresh water	0,014 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

ate		
	Marine water	0,001 mg/l
	Sewage treatment plant	3 mg/l
	Fresh water sediment	5,29 mg/kg dry weight (d.w.)
	Marine sediment	0,529 mg/kg dry weight (d.w.)
	Soil	1,05 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	83,3 mg/kg food

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,5 mm
Directive : Equipment should conform to DIN EN 374
Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Appearance	:	Pasty solid
Colour	:	beige
Odour	:	not significant
Odour Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	1,78 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Quartz (SiO₂):

Acute oral toxicity : LD50 (Rat): > 22.500 mg/kg

Tetramethylene dimethacrylate:

Acute oral toxicity : LD50 (Rat): 10.066 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Methacrylic acid, monoester with propane-1,2-diol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

1,1'-(p-tolylimino)dipropan-2-ol:

Acute oral toxicity : LD50 (Rat): > 25 - 200 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

4-tert-Butylpyrocatechol:

Acute oral toxicity : LD50 (Rat): 815 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): 1.331 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Quartz (SiO₂):

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Tetramethylene dimethacrylate:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Result : No skin irritation

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rabbit
Result : No skin irritation

1,1'-(p-tolylimino)dipropan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

4-tert-Butylpyrocatechol:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Quartz (SiO₂):

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Tetramethylene dimethacrylate:

Species : Rabbit
Result : No eye irritation

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

1,1'-(p-tolylimino)dipropan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 7 days

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

4-tert-Butylpyrocatechol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Methacrylic acid, monoester with propane-1,2-diol:

Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

1,1'-(p-tolylimino)dipropan-2-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Result : negative

4-tert-Butylpyrocatechol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Assessment : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Methacrylic acid, monoester with propane-1,2-diol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

4-tert-Butylpyrocatechol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 490
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rat
Application Route : Inhalation
Exposure time : 102 weeks
Result : negative

4-tert-Butylpyrocatechol:

Species : Rat
Application Route : Ingestion
Exposure time : 51 weeks
Result : positive
Remarks : The mechanism or mode of action is not relevant in humans.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Components:

Tetramethylene dimethacrylate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Methacrylic acid, monoester with propane-1,2-diol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

4-tert-Butylpyrocatechol:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

Quartz (SiO₂):

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Quartz (SiO₂):

Species : Humans
LOAEL : 0,053 mg/m³
Application Route : Inhalation
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Tetramethylene dimethacrylate:

Species : Rat
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 33 Days
Method : OECD Test Guideline 422

Methacrylic acid, monoester with propane-1,2-diol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Species : Rat
NOAEL : >= 300 mg/kg
Application Route : Ingestion
Exposure time : 49 Days
Method : OECD Test Guideline 422

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rat, male
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

4-tert-Butylpyrocatechol:

Species : Mouse
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Quartz (SiO₂):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 731 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Tetramethylene dimethacrylate:

Toxicity to fish : EC50 (Leuciscus idus (Golden orfe)): 32,5 mg/l
Exposure time: 48 h
Method: DIN 38412
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC10 (Desmodesmus subspicatus (green algae)): 4,35 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 9,79 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other : EC10: 7,51 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Methacrylic acid, monoester with propane-1,2-diol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 493 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 143 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 97,2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): >= 97,2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1.140 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 45,2 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

1,1'-(p-tolylimino)dipropan-2-ol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 17 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 28,8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 57,8 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 245 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 : > 1.995 mg/l
Exposure time: 30 min

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,55 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version 6.0 Revision Date: 13.01.2021 SDS Number: 1476873-00007 Date of last issue: 29.09.2020
Date of first issue: 23.03.2017

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,46 mg/l
Exposure time: 48 h
Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 7,49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,56 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,7 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

4-tert-Butylpyrocatechol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,12 mg/l
Exposure time: 96 h
Test substance: Neutralised product
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,48 mg/l
Exposure time: 48 h
Test substance: Neutralised product
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,17 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 2,29 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : 16 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,135 mg/l
Exposure time: 21 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

Partition coefficient: n-octanol/water : log Pow: 0,97

1,1'-(p-tolylimino)dipropan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 2,1

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 1.130 - 1.200
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 4,91
Remarks: Calculation

4-tert-Butylpyrocatechol:

Partition coefficient: n-octanol/water : log Pow: 1,98

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

unused product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

uncleaned packagings
15 01 10, packaging containing residues of or contaminated
by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-
hazardous products can be supplied to a system for the col-
lection of sales packaging.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parlia- : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

ment and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class : WGK 1 slightly hazardous to water
(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,7 %, 12,3 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H300 : Fatal if swallowed.
H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H361d : Suspected of damaging the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

STOT RE : Specific target organ toxicity - repeated exposure
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
2004/37/EC / TWA : Long term exposure limit
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Sens. 1

H317

Classification procedure:

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-UH 300 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 29.09.2020
6.0	13.01.2021	1476873-00007	Date of first issue: 23.03.2017

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN