

ANCHOR SELECTION

Anchor/Screw	Base material		Load			
	Non-cracked	Cracked	Static	Seismic C1	Seismic C2	Fatigue
W-VIZ Art. No. 0905 440.. 	✓	✓	✓	✓	✓	✓ ¹⁾
WIT-BS Art. No. 0905 450.. 	✓	✓	✓	-	-	-
WIT-UH 300 M Art. No. 5918 500.. 	✓	✓	✓	✓	✓	-
WIT-UH 300 R Art. No. 5918 500.. 	✓	✓	✓	✓	-	-
WIT-PE 1000 M Art. No. 5918 605.. 	✓	✓	✓	✓	✓	-
WIT-PE 1000 R Art. No. 5918 605.. 	✓	✓	✓	✓	-	-
WIT-PE 510 M Art. No. 5918 615.. 	✓	✓	✓	-	-	-
WIT-PE 510 R Art. No. 5918 615.. 	✓	✓	✓	-	-	-
WIT-VM 250 M Art. No. 0903 450.. 	✓	✓	✓	✓	-	-
WIT-VM 250 R Art. No. 0903 450.. 	✓	✓	✓	✓	-	-
WIT-PM 200 M Art. No. 5918 24.. 	✓	-	✓	-	-	-
W-BS Art. No. 5929.. 	✓ ²⁾	✓	✓	✓	✓	-
W-FAZ Art. No. 5928.. 	✓	✓	✓	✓	✓	-
W-HAZ Art. No. 0905 2.. 	✓	✓	✓	✓	✓	-
W-FA Art. No. 5932.. 	✓	-	✓	-	-	-
W-ED Art. No. 0904.. 	✓	-	✓	-	-	-

Fastening material					Fire resistance			Page number
Rebar	Steel, zinc electro plated	Steel, Hot-dipped	Stainless steel A4	High corrosion resistant steel HCR	R 120	ZTV-Ing 30/90		
						A4	HCR	
-	✓	✓	✓	✓	✓	-	✓	72
-	✓	-	✓	-	-	-	-	134
-	✓	✓	✓	✓	✓	-	-	160
✓	-	-	-	-	³⁾ -	-	-	192
-	✓	✓	✓	✓	✓	-	-	222
✓	-	-	-	-	³⁾ -	-	-	252
-	✓	✓	✓	✓	-	-	-	280
✓	-	-	-	-	³⁾ -	-	-	304
-	✓	✓	✓	✓	✓	-	-	326
✓	-	-	-	-	³⁾ -	-	-	352
-	✓	✓	✓	✓	-	-	-	376
-	✓	-	✓	✓	✓	-	-	400
-	✓	-	✓	✓	✓	-	✓	422
-	✓	-	✓	-	✓	-	-	454
-	✓	✓	✓	✓	-	-	✓	488
-	✓	-	✓	✓	✓	-	-	524